

APPLICATION / DESCRIPTION

NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIME



Specification

MODEL	LED DOWNLIGHT XZKKS
BODY MATERIAL	ALUMINUM
INPUT VOLTAGE	180-260 VAC 50Hz
LED CHIP	CREE
POWER	12W, 15W, 18W, 25W
EFFICACY	90-95 Lm/W
COLOR RENDERING INDEX	>90
LED COLOR TEMPERATURE	3000K-6500K
THDi	15%
POWER FACTOR	0.95
WORKING TEMPERATURE	0-45dg
LIGHTING SOURCE LIFE	50000Hrs
DRIVER	LIFUD

MODEL	POWER	CCT	CRI	BEAM ANGLE	INPUT LOLTAGE	DAIMENSION (MM)			MATERIAL	LED CHIP	DRIVER	PRICE
						DIAMATER	CUTTING	HEIGHT				
XZKKS12	12W	3000K-6500K	>90	15°/24°/38°	AC180-260V	65	55	90	ALUMINUM	CREE	LIFUD	฿600
XZKKS15	15W	3000K-6500K	>90	15°/24°/38°	AC180-260V	75	65	105	ALUMINUM	CREE	LIFUD	฿840
XZKKS18	18W	3000K-6500K	>90	15°/24°/38°	AC180-260V	85	75	120	ALUMINUM	CREE	LIFUD	฿1,215
XZKKS25	25W	3000K-6500K	>90	15°/24°/38°	AC180-260V	97	95	130	ALUMINUM	CREE	LIFUD	฿1,590

LED Light source

Driver

COB

WARRANTY
2Y

BEAM ANGLE
15°

BEAM ANGLE
24°

BEAM ANGLE
38°

