

APPLICATION / DESCRIPTION

NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIME



Specification

MODEL	LED DOWNLIGHT XZKES
BODY MATERIAL	ALUMINUM DIE-CASTING
INPUT VOLTAGE	180-260 VAC 50Hz
LED CHIP	CREE
POWER	7W, 12W, 22W, 28W, 40W
EFFICACY	90-95 Lm/W
COLOR RENDERING INDEX	>90
LED COLOR TEMPERATURE	3000K-6500K
THDi	15%
POWER FACTOR	0.95
WORKING TEMPERATURE	0-45dg
LIGHTING SOURCE LIFE	50000Hrs
DRIVER	LIFUD

MODEL	POWER	CCT	CRI	BEAM ANGLE	INPUT LOLTAGE	DAIMENSION (MM)			MATERIAL	LED CHIP	DRIVER	PRICE
						DIAMATER	CUTTING	HEIGHT				
XZKES07	7W	3000K-6500K	>90	15°/24°/38°	AC180-260V	85	78	70	ALUMINUM DIE-CASTING	CREE	LIFUD	฿630
XZKES12	12W	3000K-6500K	>90	15°/24°/38°	AC180-260V	110	100	90	ALUMINUM DIE-CASTING	CREE	LIFUD	฿855
XZKES22	22W	3000K-6500K	>90	15°/24°/38°	AC180-260V	125	125	120	ALUMINUM DIE-CASTING	CREE	LIFUD	฿1,455
XZKES28	28W	3000K-6500K	>90	15°/24°/38°	AC180-260V	165	145	130	ALUMINUM DIE-CASTING	CREE	LIFUD	฿1,695
XZKES40	40W	3000K-6500K	>90	15°/24°/38°	AC180-260V	190	175	160	ALUMINUM DIE-CASTING	CREE	LIFUD	฿2,430

LED Light source

Driver

COB

WARRANTY
2Y

BEAM ANGLE
15°

BEAM ANGLE
24°

BEAM ANGLE
38°

