

APPLICATION / DESCRIPTION

NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIME



Specification

MODEL	LED DOWNLIGHT XZKSSB
BODY MATERIAL	ALUMINUM
INPUT VOLTAGE	180-260 VAC 50Hz
LED CHIP	CREE
POWER	12W, 20W
EFFICACY	90-95 Lm/W
COLOR RENDERING INDEX	>90
LED COLOR TEMPERATURE	3000K-6500K
THDi	15%
POWER FACTOR	0.95
WORKING TEMPERATURE	0-45dg
LIGHTING SOURCE LIFE	50000Hrs
DRIVER	LIFUD

MODEL	POWER	CCT	CRI	BEAM ANGLE	INPUT LOLTAGE	DAIMENSION (MM)			MATERIAL	LED CHIP	DRIVER	PRICE
						DIAMATER	CUTTING	HEIGHT				
XZKSSB12	12W	3000K-6500K	>90	15°/24°/38°	AC180-260V	98	90	110	ALUMINUM	CREE	LIFUD	\$1,650
XZKSSB20	20W	3000K-6500K	>90	15°/24°/38°	AC180-260V	130	120	135	ALUMINUM	CREE	LIFUD	\$2,250

LED Light source

Driver

COB

WARRANTY2Y

BEAM ANGLE15°

BEAM ANGLE24°

BEAM ANGLE38°

