

APPLICATION / DESCRIPTION

NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIME



Specification

MODEL	LED DOWNLIGHT XZKTX
BODY MATERIAL	ALUMINUM DIE-CASTING
INPUT VOLTAGE	180-260 VAC 50Hz
LED CHIP	CREE
POWER	15W, 25W, 35W
EFFICACY	90-95 Lm/W
COLOR RENDERING INDEX	>90
LED COLOR TEMPERATURE	3000K-6500K
THDi	15%
POWER FACTOR	0.95
WORKING TEMPERATURE	0-45dg
LIGHTING SOURCE LIFE	50000Hrs
DRIVER	LIFUD

MODEL	POWER	CCT	CRI	BEAM ANGLE	INPUT LOLTAGE	DAIMENSION (MM)			MATERIAL	LED CHIP	DRIVER	PRICE
						DIAMATER	CUTTING	HEIGHT				
XZKTX15	15W	3000K-6500K	>90	15°/24°/38°	AC180-260V	65	110	-	ALUMINUM DIE-CASTING	CREE	LIFUD	฿1,215
XZKTX25	25W	3000K-6500K	>90	15°/24°/38°	AC180-260V	75	125	-	ALUMINUM DIE-CASTING	CREE	LIFUD	฿1,500
XZKTX35	35W	3000K-6500K	>90	15°/24°/38°	AC180-260V	90	145	-	ALUMINUM DIE-CASTING	CREE	LIFUD	฿1,650

LED Light source

Driver

COB

WARRANTY
2Y

BEAM ANGLE
15°

BEAM ANGLE
24°

BEAM ANGLE
38°

