



LED BULB 5W XZLEN

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES
- * WITH MANY COLOR TO MAKE GOOD ATMOSPHERE
- * HAVE WHITE OR MULTI-LIGHT THAT APPROPRIATE FOR SHOWCASES, DISPLAY WINDOWS, MODERN SHOP, ETC

SPECIFICATION

BODY MATERIAL	: PLASTIC + ALUMINUM
INPUT VOLTAGE	: 180-260 VAC
LED CHIP	: SMD
POWER	: 5W
LUMINOUS FLUX	: 450lm
EFFICACY	: 90lm/w
COLOR RENDERING INDEX	: 80
LED COLOR TEMPERATURE	: 6000K
VIEW ANGLE	: 200°
THDi	: <15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10-50°C
LIGHTING SOURCE LIFE	: >50,000Hrs



STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:

RADIO DISTURBANCE LIMITS

ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE

RoHS

MODEL	LAMP		DIMENSION (mm.)		REMARK
	WATT	TYPE	Ø	H	
XZ-B-5W	5	SMD LED	60	108	



LED BULB 7W XZLEN

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES
- * WITH MANY COLOR TO MAKE GOOD ATMOSPHERE
- * HAVE WHITE OR MULTI-LIGHT THAT APPROPRIATE FOR SHOWCASES, DISPLAY WINDOWS, MODERN SHOP, ETC



SPECIFICATION

BODY MATERIAL	: PLASTIC + ALUMINUM
INPUT VOLTAGE	: 180-260 VAC
LED CHIP	: SMD
POWER	: 7W
LUMINOUS FLUX	: 630lm
EFFICACY	: 90lm/w
COLOR RENDERING INDEX	: 80
LED COLOR TEMPERATURE	: 6000K
VIEW ANGLE	: 200°
THDi	: <15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10-50°C
LIGHTING SOURCE LIFE	: >50,000Hrs

STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:

RADIO DISTURBANCE LIMITS

ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE

RoHS

MODEL	LAMP		DIMENSION (mm.)		REMARK
	WATT	TYPE	Ø	H	
XZ-B-7W	7	SMD LED	70	122	



LED BULB 9W XZLEN

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES
- * WITH MANY COLOR TO MAKE GOOD ATMOSPHERE
- * HAVE WHITE OR MULTI-LIGHT THAT APPROPRIATE FOR SHOWCASES, DISPLAY WINDOWS, MODERN SHOP, ETC

SPECIFICATION

BODY MATERIAL	: PLASTIC + ALUMINUM
INPUT VOLTAGE	: 180-260 VAC
LED CHIP	: SMD
POWER	: 9W
LUMINOUS FLUX	: 800lm
EFFICACY	: 90lm/w
COLOR RENDERING INDEX	: 80
LED COLOR TEMPERATURE	: 6000K
VIEW ANGLE	: 200°
THDi	: <15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10-50°C
LIGHTING SOURCE LIFE	: >50,000Hrs



STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:

RADIO DISTURBANCE LIMITS

ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE

RoHS

MODEL	LAMP		DIMENSION (mm.)		REMARK
	WATT	TYPE	Ø	H	
XZ-B-9W	9	SMD LED	80	137	



LED BULB 12W XZLEN

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES
- * WITH MANY COLOR TO MAKE GOOD ATMOSPHERE
- * HAVE WHITE OR MULTI-LIGHT THAT APPROPRIATE FOR SHOWCASES, DISPLAY WINDOWS, MODERN SHOP, ETC

SPECIFICATION

BODY MATERIAL	: PLASTIC + ALUMINUM
INPUT VOLTAGE	: 180-260 VAC
LED CHIP	: SMD
POWER	: 12W
LUMINOUS FLUX	: 1080lm
EFFICACY	: 90lm/w
COLOR RENDERING INDEX	: 80
LED COLOR TEMPERATURE	: 6000K
VIEW ANGLE	: 200°
THDi	: <15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10-50°C
LIGHTING SOURCE LIFE	: >50,000Hrs



STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:

RADIO DISTURBANCE LIMITS

ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE

RoHS

MODEL	LAMP		DIMENSION (mm.)		REMARK
	WATT	TYPE	Ø	H	
XZ-B-12W	12	SMD LED	80	137	