

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY
 AND LONG DURATION TIMES
- * WITH MANY COLOR TO MAKE GOOD ATMOSPHERE
- * HAVE WHITE OR MULTI-LIGHT THAT APPROPIATE FOR SHOWCASES, DISPLAY WINDOWS, MODERN SHOP, ETC

SPECIFICATION

BODY MATERIAL : GLASS AND ALUMINIUM

INPUT VOLTAGE : 180-245 VAC ,50 Hz.

LED CHIP : EPISTAR

POWER : 6W

LUMINOUS FLUX : 600lm

EFFICACY : 100lm/w

COLOR RENDERING INDEX : >80

LED COLOR TEMPERATURE : 2200K-6500K

VIEW ANGLE : 360°

THDi : <15%

POWER FACTOR : >0.95

WORKING TEMPERATURE : -10-50°C

LIGHTING SOURCE LIFE : >50,000Hrs

LAMP TERMINAL : E27

STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:

RADIO DISTURBANCE LIMITS

ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE

RoHS

MODEL	LAMP		DIMENSION (mm.)			WEIGH	REMARK
	WATT	TYPE	W	L	Н	Kg.	REMARK
ST64-T6	6	SMD LED	64	64	140	0.076	FOR REPLECMENT INCANDESCENT 30-50W



