

STREET LIGHT 60W Modeal : XZ-SL-03Y

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY
 AND LONG DURATION TIMES
- * WITH MANY COLOR TO MAKE GOOD ATMOSPHERE
- * HAVE WHITE OR MULTI-LIGHT THAT APPROPIATE FOR SHOWCASES, DISPLAY WINDOWS, MODERN SHOP, ETC



MATERIAL : Aluminum + lens

INPUT VOLTAGE : 85-305 VAC

LED CHIP : SMD

POWER : 60W

LUMINOUS FLUX : 7200 lm

EFFICACY : 120 lm/W

COLOR RENDERING INDEX : >70

LED COLOR TEMPERATURE : 2700-6500K

THDi : <15%

POWER FACTOR : >0.95

WORKING TEMPERATURE : -10-50°C

LIGHTING SOURCE LIFE : >50,000Hrs





STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:

RADIO DISTURBANCE LIMITS

ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE

RoHS

MODEL	LAMP		HOLE CUT(mm)			WEIGH	REMARK
	WATT	TYPE	W	L	Н	Kg	REMARK
XZ-SL-03Y	60	SMD				7	



STREET LIGHT 100W Modeal: XZ-SL-03Y

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY
 AND LONG DURATION TIMES
- * WITH MANY COLOR TO MAKE GOOD ATMOSPHERE
- * HAVE WHITE OR MULTI-LIGHT THAT APPROPIATE FOR SHOWCASES, DISPLAY WINDOWS, MODERN SHOP, ETC



MATERIAL : Aluminum + lens

INPUT VOLTAGE : 85-305 VAC

LED CHIP : SMD

POWER : 100W

LUMINOUS FLUX : 12000 lm

EFFICACY : 120 lm/W

COLOR RENDERING INDEX : >70

LED COLOR TEMPERATURE : 2700-6500K

THDi : <15%

POWER FACTOR : >0.95

WORKING TEMPERATURE : -10-50°C

LIGHTING SOURCE LIFE : >50,000Hrs





STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:

RADIO DISTURBANCE LIMITS

ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE

RoHS

MODEL	LAMP		HOLE CUT(mm)			WEIGH	REMARK
	WATT	TYPE	W	L	Н	Kg	REMARK
XZ-SL-03Y	100	SMD				7	



STREET LIGHT 150W Modeal: XZ-SL-03Y

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY
 AND LONG DURATION TIMES
- * WITH MANY COLOR TO MAKE GOOD ATMOSPHERE
- * HAVE WHITE OR MULTI-LIGHT THAT APPROPIATE FOR SHOWCASES, DISPLAY WINDOWS, MODERN SHOP, ETC



MATERIAL : Aluminum + lens

INPUT VOLTAGE : 85-305 VAC

LED CHIP : SMD

POWER : 150W

LUMINOUS FLUX : 18000 lm

EFFICACY : 120 lm/W

COLOR RENDERING INDEX : >70

LED COLOR TEMPERATURE : 2700-6500K

THDi : <15%

POWER FACTOR : >0.95

WORKING TEMPERATURE : -10-50°C

LIGHTING SOURCE LIFE : >50,000Hrs





STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:

RADIO DISTURBANCE LIMITS

ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE

RoHS

MODEL	LAMP		HOLE CUT(mm)			WEIGH	REMARK
	WATT	TYPE	W	L	Н	Kg	REWARK
XZ-SL-03Y	150	SMD				9.5	