

Promotion sale solar sensor led flood light quotaitons

No.	Modle	PICTURTES	POWER	FUNCTION	SPECIFICATION
					PARAMETERS
1	XZ-TYNTGD-20W		20W	1. Lamp body material: Die-cast aluminum 2. Solar Panel Category: Polysilicon 3. Battery Type: Lithium Battery 4. Working temperature: -30 - +60 5. Storage temperature: -30 - +60 6. Discharge time: 8-12 hours (optional) 7. Recommended installation height: 3-5m 8. Rainy weather lighting time: 3 days 9. Warranty: 2 years 10. Light source type: 2835 dual chip patch 11. Work mode: intelligent control lighting mode	LED CHIP: Epistar 2835smd
					lithium battery: 3.7V 4.4Ah
					Polycrystalline solar panels: 6W 6V
					solar panel size : 220*17*130mm
					Material: ABS plastic shell
					lamp size: 180*52*210mm
					Net weight : 1.2KG
					ctn size: 75.5*19.*23.5CM
					qty/ctn: 10/PCS
					G.W: 13.0
2	XZ-TYNTGD-30W		30W	1. Lamp body material: Die-cast aluminum 2. Solar Panel Category: Polysilicon 3. Battery Type: Lithium Battery 4. Working temperature: -30 - +60 5. Storage temperature: -30 - +60 6. Discharge time: 8-12 hours (optional) 7. Recommended installation height: 3-5m 8. Rainy weather lighting time: 3 days 9. Warranty: 2 years 10. Light source type: 2835 dual chip patch 11. Work mode: intelligent control lighting mode	LED CHIP: Epistar 2835smd
					lithium battery: 3.7V 8.8Ah
					Polycrystalline solar panels: 8W 6V
					solar panel size : 220*17*190mm
					Material: ABS plastic shell
					lamp size: 192*52*237mm
					Net weight : 1.7KG
					ctn size: 75.5*20.5*25.5CM
					qty/ctn: 10/PCS
					G.W: 18.0
3	XZ-TYNTGD-50W		50W	1. Lamp body material: Die-cast aluminum 2. Solar Panel Category: Polysilicon 3. Battery Type: Lithium Battery 4. Working temperature: -30 - +60 5. Storage temperature: -30 - +60 6. Discharge time: 8-12 hours (optional) 7. Recommended installation height: 3-5m 8. Rainy weather lighting time: 3 days 9. Warranty: 2 years 10. Light source type: 2835 dual chip patch 11. Work mode: intelligent control lighting mode	LED CHIP: Epistar 2835smd
					lithium battery: 3.7V 12Ah
					Polycrystalline solar panels: 10W 6V
					solar panel size : 350*17*230mm
					Material: ABS plastic shell
					lamp size: 230*59*285mm
					Net weight : 2.5KG
					ctn size: 38.5*38.5*29.5CM
					qty/ctn: 5/PCS
					G.W: 13.0
4	XZ-TYNTGD-100W		100W	1. Lamp body material: Die-cast aluminum 2. Solar Panel Category: Polysilicon 3. Battery Type: Lithium Battery 4. Working temperature: -30 - +60 5. Storage temperature: -30 - +60 6. Discharge time: 8-12 hours (optional) 7. Recommended installation height: 3-5m 8. Rainy weather lighting time: 3 days 9. Warranty: 2 years 10. Light source type: 2835 dual chip patch 11. Work mode: intelligent control lighting mode	LED CHIP: Epistar 2835smd
					lithium battery: 7.4V 10Ah
					Polycrystalline solar panels: 20W 12V
					solar panel size : 355*25*330mm
					Material: ABS plastic shell
					lamp size: 280*70*335mm
					Net weight : 3.2KG
					ctn size: 57*57.5*34.5CM
					qty/ctn: 5/PCS
					G.W: 16.5