

APPLICATION / DESCRIPTION

NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIME



Specification

MODEL	LED DOWNLIGHT XZKDS
BODY MATERIAL	ALUMINUM + IRON
INPUT VOLTAGE	180-260 VAC 50Hz
LED CHIP	CREE
POWER	7W, 14W, 21W
EFFICACY	90-95 Lm/W
COLOR RENDERING INDEX	>90
LED COLOR TEMPERATURE	3000K-6500K
THDi	15%
POWER FACTOR	0.95
WORKING TEMPERATURE	0-45dg
LIGHTING SOURCE LIFE	50000Hrs
DRIVER	LIFUD

MODEL	POWER	CCT	CRI	BEAM ANGLE	INPUT LOLTAGE	DAIMENSION (MM)			MATERIAL	LED CHIP	DRIVER	PRICE
						DIAMATER	CUTTING	HEIGHT				
XZKDS07	7W	3000K-6500K	>90	15°/24°/38°	AC180-260V	105*105	95*95	-	ALUMINUM + IRON	CREE	LIFUD	฿840
XZKDS14	7W*2	3000K-6500K	>90	15°/24°/38°	AC180-260V	205*105	190*95	-	ALUMINUM + IRON	CREE	LIFUD	฿1,350
XZKDS21	7W*3	3000K-6500K	>90	15°/24°/38°	AC180-260V	290*105	280*95	-	ALUMINUM + IRON	CREE	LIFUD	฿1,905

LED Light source



Driver

