



FLOOD LIGHT RITA 400W

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES
- * WITH MANY COLOR TO MAKE GOOD ATMOSPHERE
- * HAVE WHITE OR MULTI-LIGHT THAT APPROPRIATE FOR SHOWCASES, DISPLAY WINDOWS, MODERN SHOP, ETC

SPECIFICATION

MATERIAL	: Aluminum + lens
INPUT VOLTAGE	: 85-305 VAC
LED CHIP	: SMD
POWER	: 400W
LUMINOUS FLUX	: 48000 lm
EFFICACY	: 120 lm/W
COLOR RENDERING INDEX	: >70
LED COLOR TEMPERATURE	: 3000-6500K
THDi	: <15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10-50°C
LIGHTING SOURCE LIFE	: >50,000Hrs



STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:
 RADIO DISTURBANCE LIMITS
 ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE
 RoHS

MODEL	LAMP		HOLE CUT(mm)			WEIGH	REMARK
	WATT	TYPE	W	L	H	Kg	
XZ-FLR400	400	SMD	593	91	621	19	



FLOOD LIGHT RITA 500W

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES
- * WITH MANY COLOR TO MAKE GOOD ATMOSPHERE
- * HAVE WHITE OR MULTI-LIGHT THAT APPROPRIATE FOR SHOWCASES, DISPLAY WINDOWS, MODERN SHOP, ETC

SPECIFICATION

MATERIAL	: Aluminum + lens
INPUT VOLTAGE	: 85-305 VAC
LED CHIP	: SMD
POWER	: 500W
LUMINOUS FLUX	: 60000 lm
EFFICACY	: 120 lm/W
COLOR RENDERING INDEX	: >70
LED COLOR TEMPERATURE	: 3000-6500K
THDi	: <15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10-50°C
LIGHTING SOURCE LIFE	: >50,000Hrs



STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:
 RADIO DISTURBANCE LIMITS
 ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE
 RoHS

MODEL	LAMP		HOLE CUT(mm)			WEIGH Kg	REMARK
	WATT	TYPE	W	L	H		
XZ-FLR500	500	SMD	811	117	606	27	



FLOOD LIGHT RITA 600W

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES
- * WITH MANY COLOR TO MAKE GOOD ATMOSPHERE
- * HAVE WHITE OR MULTI-LIGHT THAT APPROPRIATE FOR SHOWCASES, DISPLAY WINDOWS, MODERN SHOP, ETC

SPECIFICATION

MATERIAL	: Aluminum + lens
INPUT VOLTAGE	: 85-305 VAC
LED CHIP	: SMD
POWER	: 600W
LUMINOUS FLUX	: 70500 lm
EFFICACY	: 120 lm/W
COLOR RENDERING INDEX	: >70
LED COLOR TEMPERATURE	: 3000-6500K
THDi	: <15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10-50°C
LIGHTING SOURCE LIFE	: >50,000Hrs



STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:
 RADIO DISTURBANCE LIMITS
 ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE
 RoHS

MODEL	LAMP		HOLE CUT(mm)			WEIGH	REMARK
	WATT	TYPE	W	L	H	Kg	
XZ-FLR600	600	SMD	811	117	606	27.5	