



LED BULB 6W FILAMENT

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES
- * WITH MANY COLOR TO MAKE GOOD ATMOSPHERE
- * HAVE WHITE OR MULTI-LIGHT THAT APPROPRIATE FOR SHOWCASES, DISPLAY WINDOWS, MODERN SHOP, ETC



SPECIFICATION

BODY MATERIAL	: PLASTIC BAG ALUMINUM
INPUT VOLTAGE	: 180-245 VAC ,50 Hz.
LED CHIP	: EPISTAR
POWER	: 6W
LUMINOUS FLUX	: 600lm
EFFICACY	: 100lm/w
COLOR RENDERING INDEX	: 80
LED COLOR TEMPERATURE	: 6500K
VIEW ANGLE	: 360°
THDi	: <15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10-50°C
LIGHTING SOURCE LIFE	: >50,000Hrs



STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:

RADIO DISTURBANCE LIMITS

ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE

RoHS

MODEL	LAMP		DIMENSION (mm.)			WEIGH	REMARK
	WATT	TYPE	W	L	H	Kg.	
GG125-G6	6	SMD LED	125	125	175	0.068	FOR REPLECMENT INCANDESCENT 30-50W



LED BULB 8W FILAMENT

APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES
- * WITH MANY COLOR TO MAKE GOOD ATMOSPHERE
- * HAVE WHITE OR MULTI-LIGHT THAT APPROPRIATE FOR SHOWCASES, DISPLAY WINDOWS, MODERN SHOP, ETC



SPECIFICATION

BODY MATERIAL	: PLASTIC BAG ALUMINUM
INPUT VOLTAGE	: 180-245 VAC ,50 Hz.
LED CHIP	: EPISTAR
POWER	: 8W
LUMINOUS FLUX	: 800lm
EFFICACY	: 100lm/w
COLOR RENDERING INDEX	: 80
LED COLOR TEMPERATURE	: 6500K
VIEW ANGLE	: 360°
THDi	: <15%
POWER FACTOR	: >0.95
WORKING TEMPERATURE	: -10-50°C
LIGHTING SOURCE LIFE	: >50,000Hrs



STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:

RADIO DISTURBANCE LIMITS

ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE

RoHS

MODEL	LAMP		DIMENSION (mm.)			WEIGH	REMARK
	WATT	TYPE	W	L	H	Kg.	
GG125-G8	8	SMD LED	125	125	175	0.068	FOR REPLECMENT INCANDESCENT 30-50W