



APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES
- * WITH MANY COLOR TO MAKE GOOD ATMOSPHERE
- * HAVE WHITE OR MULTI-LIGHT THAT APPROPRIATE FOR SHOWCASES, DISPLAY WINDOWS, MODERN SHOP, ETC

SPECIFICATION

MATERIAL	: ALUMINIUM + LENS
INPUT VOLTAGE	: 18 VDC
LED CHIP	: SMD
POWER	: 15W
LUMINOUS FLUX	: 1950 lm
EFFICACY	: 130 lm/W
COLOR RENDERING INDEX	: >70
LED COLOR TEMPERATURE	: 2700-6500K
THDi	: <15%
POWER FACTOR	: >0.95
SOLAR PANEL (SUGGEST)	: 18V 40W
LIGHTING SOURCE LIFE	: >50,000Hrs
BATTERRY	: >1YEAR
IP	: IP65

STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:

RADIO DISTURBANCE LIMITS

ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE

RoHS

STREETLIGHT SOLAR 15W Model : XZ-U15W-A



MODEL	LAMP		HOLE CUT(mm)			WEIGH	REMARK
	WATT	TYPE	W	L	H	Kg	
XZ-U15W-A	15	SMD					6 Hrs 100% + 6 Hrs 50%



APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES
- * WITH MANY COLOR TO MAKE GOOD ATMOSPHERE
- * HAVE WHITE OR MULTI-LIGHT THAT APPROPRIATE FOR SHOWCASES, DISPLAY WINDOWS, MODERN SHOP, ETC

SPECIFICATION

MATERIAL	: ALUMINIUM + LENS
INPUT VOLTAGE	: 18 VDC
LED CHIP	: SMD
POWER	: 15W
LUMINOUS FLUX	: 1950 lm
EFFICACY	: 130 lm/W
COLOR RENDERING INDEX	: >70
LED COLOR TEMPERATURE	: 2700-6500K
THDi	: <15%
POWER FACTOR	: >0.95
SOLAR PANEL (SUGGEST)	: 18V 45W
LIGHTING SOURCE LIFE	: >50,000Hrs
BATTERRY	: >1YEAR
IP	: IP65

STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:

RADIO DISTURBANCE LIMITS

ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE

RoHS

STREETLIGHT SOLAR 15W Model : XZ-U15W-B



MODEL	LAMP		HOLE CUT(mm)			WEIGH	REMARK
	WATT	TYPE	W	L	H	Kg	
XZ-U15W-B	15	SMD					50% + 100% RADOR SENCOR



APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES
- * WITH MANY COLOR TO MAKE GOOD ATMOSPHERE
- * HAVE WHITE OR MULTI-LIGHT THAT APPROPRIATE FOR SHOWCASES, DISPLAY WINDOWS, MODERN SHOP, ETC

SPECIFICATION

MATERIAL	: ALUMINIUM + LENS
INPUT VOLTAGE	: 18 VDC
LED CHIP	: SMD
POWER	: 20W
LUMINOUS FLUX	: 2600 lm
EFFICACY	: 130 lm/W
COLOR RENDERING INDEX	: >70
LED COLOR TEMPERATURE	: 2700-6500K
THDi	: <15%
POWER FACTOR	: >0.95
SOLAR PANEL (SUGGEST)	: 18V 50W
LIGHTING SOURCE LIFE	: >50,000Hrs
BATTERRY	: >1YEAR
IP	: IP65

STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:

RADIO DISTURBANCE LIMITS

ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE

RoHS

STREETLIGHT SOLAR 20W Model : XZ-U20W-A



REMOTE
SETTING



MC4 PLUG IN
CONNECTION

MODEL	LAMP		HOLE CUT(mm)			WEIGH Kg	REMARK
	WATT	TYPE	W	L	H		
XZ-U20W-A	20	SMD					6 Hrs 100% + 6 Hrs 50%



APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES
- * WITH MANY COLOR TO MAKE GOOD ATMOSPHERE
- * HAVE WHITE OR MULTI-LIGHT THAT APPROPRIATE FOR SHOWCASES, DISPLAY WINDOWS, MODERN SHOP, ETC

SPECIFICATION

MATERIAL	: ALUMINIUM + LENS
INPUT VOLTAGE	: 18 VDC
LED CHIP	: SMD
POWER	: 20W
LUMINOUS FLUX	: 2600 lm
EFFICACY	: 130 lm/W
COLOR RENDERING INDEX	: >70
LED COLOR TEMPERATURE	: 2700-6500K
THDi	: <15%
POWER FACTOR	: >0.95
SOLAR PANEL (SUGGEST)	: 18V 50W
LIGHTING SOURCE LIFE	: >50,000Hrs
BATTERRY	: >1YEAR
IP	: IP65

STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:

RADIO DISTURBANCE LIMITS

ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE

RoHS

STREETLIGHT SOLAR 20W Model : XZ-U20W-B



MODEL	LAMP		HOLE CUT(mm)			WEIGH	REMARK
	WATT	TYPE	W	L	H	Kg	
XZ-U20W-B	20	SMD					50% + 100% RADOR SENCOR



APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES
- * WITH MANY COLOR TO MAKE GOOD ATMOSPHERE
- * HAVE WHITE OR MULTI-LIGHT THAT APPROPRIATE FOR SHOWCASES, DISPLAY WINDOWS, MODERN SHOP, ETC

SPECIFICATION

MATERIAL	: ALUMINIUM + LENS
INPUT VOLTAGE	: 18 VDC
LED CHIP	: SMD
POWER	: 25W
LUMINOUS FLUX	: 3250 lm
EFFICACY	: 130 lm/W
COLOR RENDERING INDEX	: >70
LED COLOR TEMPERATURE	: 2700-6500K
THDi	: <15%
POWER FACTOR	: >0.95
SOLAR PANEL (SUGGEST)	: 18V 60W
LIGHTING SOURCE LIFE	: >50,000Hrs
BATTERRY	: >1YEAR
IP	: IP65

STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:

RADIO DISTURBANCE LIMITS

ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE

RoHS

STREETLIGHT SOLAR 25W Model : XZ-U25W-A



REMOTE
SETTING



MC4 PLUG IN
CONNECTION

MODEL	LAMP		HOLE CUT(mm)			WEIGH	REMARK
	WATT	TYPE	W	L	H	Kg	
XZ-U25W-A	25	SMD					6 Hrs 100% + 6 Hrs 50%



APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES
- * WITH MANY COLOR TO MAKE GOOD ATMOSPHERE
- * HAVE WHITE OR MULTI-LIGHT THAT APPROPRIATE FOR SHOWCASES, DISPLAY WINDOWS, MODERN SHOP, ETC

SPECIFICATION

MATERIAL	: ALUMINIUM + LENS
INPUT VOLTAGE	: 18 VDC
LED CHIP	: SMD
POWER	: 30W
LUMINOUS FLUX	: 3900 lm
EFFICACY	: 130 lm/W
COLOR RENDERING INDEX	: >70
LED COLOR TEMPERATURE	: 2700-6500K
THDi	: <15%
POWER FACTOR	: >0.95
SOLAR PANEL (SUGGEST)	: 18V 70W
LIGHTING SOURCE LIFE	: >50,000Hrs
BATTERRY	: >1YEAR
IP	: IP65

STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:

RADIO DISTURBANCE LIMITS

ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE

RoHS

STREETLIGHT SOLAR 30W Model : XZ-U30W-A



REMOTE
SETTING



MC4 PLUG IN
CONNECTION

MODEL	LAMP		HOLE CUT(mm)			WEIGH Kg	REMARK
	WATT	TYPE	W	L	H		
XZ-U30W-A	30	SMD					6 Hrs 100% + 6 Hrs 50%



APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES
- * WITH MANY COLOR TO MAKE GOOD ATMOSPHERE
- * HAVE WHITE OR MULTI-LIGHT THAT APPROPRIATE FOR SHOWCASES, DISPLAY WINDOWS, MODERN SHOP, ETC

SPECIFICATION

MATERIAL	: ALUMINIUM + LENS
INPUT VOLTAGE	: 18 VDC
LED CHIP	: SMD
POWER	: 30W
LUMINOUS FLUX	: 3900 lm
EFFICACY	: 130 lm/W
COLOR RENDERING INDEX	: >70
LED COLOR TEMPERATURE	: 2700-6500K
THDi	: <15%
POWER FACTOR	: >0.95
SOLAR PANEL (SUGGEST)	: 18V 50W
LIGHTING SOURCE LIFE	: >50,000Hr
BATTERRY	: >1YEAR
IP	: IP65

STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:

RADIO DISTURBANCE LIMITS

ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE

RoHS

STREETLIGHT SOLAR 30W Model : XZ-U30W-B



MODEL	LAMP		HOLE CUT(mm)			WEIGH	REMARK
	WATT	TYPE	W	L	H	Kg	
XZ-U30W-B	30	SMD					50% + 100% RADOR SENCOR



APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES
- * WITH MANY COLOR TO MAKE GOOD ATMOSPHERE
- * HAVE WHITE OR MULTI-LIGHT THAT APPROPRIATE FOR SHOWCASES, DISPLAY WINDOWS, MODERN SHOP, ETC

SPECIFICATION

MATERIAL	: ALUMINIUM + LENS
INPUT VOLTAGE	: 18 VDC
LED CHIP	: SMD
POWER	: 35W
LUMINOUS FLUX	: 4550 lm
EFFICACY	: 130 lm/W
COLOR RENDERING INDEX	: >70
LED COLOR TEMPERATURE	: 2700-6500K
THDi	: <15%
POWER FACTOR	: >0.95
SOLAR PANEL (SUGGEST)	: 18V 80W
LIGHTING SOURCE LIFE	: >50,000Hrs
BATTERRY	: >1YEAR
IP	: IP65

STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:

RADIO DISTURBANCE LIMITS

ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE

RoHS

STREETLIGHT SOLAR 35W Model : XZ-U35W-A



MODEL	LAMP		HOLE CUT(mm)			WEIGH	REMARK
	WATT	TYPE	W	L	H	Kg	
XZ-U35W-A	35	SMD					6 Hrs 100% + 6 Hrs 50%



APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES
- * WITH MANY COLOR TO MAKE GOOD ATMOSPHERE
- * HAVE WHITE OR MULTI-LIGHT THAT APPROPRIATE FOR SHOWCASES, DISPLAY WINDOWS, MODERN SHOP, ETC

SPECIFICATION

MATERIAL	: ALUMINIUM + LENS
INPUT VOLTAGE	: 18 VDC
LED CHIP	: SMD
POWER	: 40W
LUMINOUS FLUX	: 4550 lm
EFFICACY	: 130 lm/W
COLOR RENDERING INDEX	: >70
LED COLOR TEMPERATURE	: 2700-6500K
THDi	: <15%
POWER FACTOR	: >0.95
SOLAR PANEL (SUGGEST)	: 18V 90W
LIGHTING SOURCE LIFE	: >50,000Hrs
BATTERRY	: >1YEAR
IP	: IP65

STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:

RADIO DISTURBANCE LIMITS

ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE

RoHS

STREETLIGHT SOLAR 40W Model : XZ-U40W-A



MODEL	LAMP		HOLE CUT(mm)			WEIGH	REMARK
	WATT	TYPE	W	L	H	Kg	
XZ-U40W-A	40	SMD					6 Hrs 100% + 6 Hrs 50%



APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES
- * WITH MANY COLOR TO MAKE GOOD ATMOSPHERE
- * HAVE WHITE OR MULTI-LIGHT THAT APPROPRIATE FOR SHOWCASES, DISPLAY WINDOWS, MODERN SHOP, ETC

SPECIFICATION

MATERIAL	: ALUMINIUM + LENS
INPUT VOLTAGE	: 18 VDC
LED CHIP	: SMD
POWER	: 40W
LUMINOUS FLUX	: 5200 lm
EFFICACY	: 130 lm/W
COLOR RENDERING INDEX	: >70
LED COLOR TEMPERATURE	: 2700-6500K
THDi	: <15%
POWER FACTOR	: >0.95
SOLAR PANEL (SUGGEST)	: 18V 80W
LIGHTING SOURCE LIFE	: >50,000Hrs
BATTERRY	: >1YEAR
IP	: IP65

STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:

RADIO DISTURBANCE LIMITS

ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE

RoHS

STREETLIGHT SOLAR 40W Model : XZ-U40W-B



MODEL	LAMP		HOLE CUT(mm)			WEIGH	REMARK
	WATT	TYPE	W	L	H	Kg	
XZ-U40W-B	40	SMD					50% + 100% RADOR SENCOR



APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES
- * WITH MANY COLOR TO MAKE GOOD ATMOSPHERE
- * HAVE WHITE OR MULTI-LIGHT THAT APPROPRIATE FOR SHOWCASES, DISPLAY WINDOWS, MODERN SHOP, ETC

SPECIFICATION

MATERIAL	: ALUMINIUM + LENS
INPUT VOLTAGE	: 18 VDC
LED CHIP	: SMD
POWER	: 50W
LUMINOUS FLUX	: 6500 lm
EFFICACY	: 130 lm/W
COLOR RENDERING INDEX	: >70
LED COLOR TEMPERATURE	: 2700-6500K
THDi	: <15%
POWER FACTOR	: >0.95
SOLAR PANEL (SUGGEST)	: 18V 100W
LIGHTING SOURCE LIFE	: >50,000Hrs
BATTERRY	: >1YEAR
IP	: IP65

STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:

RADIO DISTURBANCE LIMITS

ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE

RoHS

STREETLIGHT SOLAR 50W Model : XZ-U50W-A



REMOTE
SETTING



MC4 PLUG IN
CONNECTION

MODEL	LAMP		HOLE CUT(mm)			WEIGH Kg	REMARK
	WATT	TYPE	W	L	H		
XZ-U50W-A	50	SMD					6 Hrs 100% + 6 Hrs 50%



APPLICATION/DESCRIPTION

- * NEW DESIGN OR REPLACE OLD LAMP TO SAVING ENERGY AND LONG DURATION TIMES
- * WITH MANY COLOR TO MAKE GOOD ATMOSPHERE
- * HAVE WHITE OR MULTI-LIGHT THAT APPROPRIATE FOR SHOWCASES, DISPLAY WINDOWS, MODERN SHOP, ETC

SPECIFICATION

MATERIAL	: ALUMINIUM + LENS
INPUT VOLTAGE	: 18 VDC
LED CHIP	: SMD
POWER	: 60W
LUMINOUS FLUX	: 7800 lm
EFFICACY	: 130 lm/W
COLOR RENDERING INDEX	: >70
LED COLOR TEMPERATURE	: 2700-6500K
THDi	: <15%
POWER FACTOR	: >0.95
SOLAR PANEL (SUGGEST)	: 18V 110W
LIGHTING SOURCE LIFE	: >50,000Hrs
BATTERRY	: >1YEAR
IP	: IP65

STANDARD

TIS. 1955-2551 LIGHTING AND SIMILAR EQUIPMENT:

RADIO DISTURBANCE LIMITS

ISO 9001 CERTIFIED FOR QUALITY CONTROL GUARANTEE

RoHS

STREETLIGHT SOLAR 60W Model : XZ-U60W-A



REMOTE
SETTING



MC4 PLUG IN
CONNECTION

MODEL	LAMP		HOLE CUT(mm)			WEIGH	REMARK
	WATT	TYPE	W	L	H	Kg	
XZ-U60W-A	60	SMD					6 Hrs 100% + 6 Hrs 50%